

Rejuva® Roof coating

Water based roof coating that improves the functionality, appearance and look of roof tiles.

Recommended for All mineral roof tiles like concrete, clay, and fibro cement.

Description: Rejuva® is a unique roof coating continually developed and based on the latest technology available on the market. It is a two-coat technology system, which has ultrathin molecules that penetrate deep and bond to the roof tile surface. The technology used for Rejuva Roof Coating makes it extremely hydrophobic and performs with a low water absorption rate, while the roof surface remains permeable to water vapour. Furthermore the Rejuva Roof Coating is extremely resistant to UV radiation and protects the roof tiles from break down due to the sun and other weather influences.

Recommendation: On surfaces of fibre cement we recommend to apply Rejuva Primer before treating with Rejuva Roof Coating. For details about Rejuva Primer see the separate data sheet. Preparation Ensure the surface is clean and free from contamination. Use high pressure cleaning to ensure a durable clean surface. All loose particles have to be removed.

Application:

- Use an airless sprayer for application.
- In case of high porosity of the surface it is recommended to apply Rejuva Primer.
- 1st Coat – due to the heat and porosity of the roof tiles, if necessary and no primer has been applied, dilute up to 20% with water.
- 2nd Coat - apply undiluted. A minimum temperature of 5 °C is required for the application.

Coverage rate: 150-200ml per m² and coat, depending on the porosity.

Rainproof: 30 – 60 minutes under average conditions at 20°C (substrate and temperature dependent).

Packaging: 20 KG pot (24 pots/pallet)

Colours: Black, anthracite grey, dark brown, tile red, red brown, etc.

Equipment care: All equipment should be cleaned up in water directly after its use.

Storage: Store away from direct sunlight, sources of heat and protected from frost.

Shelf life: 24 months (in original sealed container).

Safety and Regulations:

Not classified as hazardous according to current labelling. For full information regarding handling precautions please consult the material security data sheet and the product label.

Properties and Advantages

- Rejuva improves the functionality and look of the roof
- Long durability – UV resistant and low on water absorption
- Ultrathin molecules – great surface bonding
- Hydrophobic - water runs off more easily
- Permanent flexibility
- High covering power – 20% better than average
- Water based
- Environmentally friendly
- Minimizes the growth of moss and algae
- Saves time and money
- Water permeability according to DIN EN 1062-3 - Passed
- Water vapour diffusion according to vDIN EN ISO7783-2 - Passed
- Flexibility according to DIN 53504-2 - Passed
- Accelerated Weathering - Passed



Status: July 2018. This BECO TREAT ApS information was compiled according to the state of the art and our present experience. It is intended to support craftsmen in selecting the proper materials and using them correctly. The information provided here does not release the user from the responsibility for checking the material for its suitability for the intended application, considering all object-related factors. New editions replace the information given here.